

ICONIK 260D

TECHNICAL DATA VINYL FLOORING 2020

Classification	Norm	Tarkett Value
Product type	EN ISO 26986	Expanded (cushioned) poly(vinyl chloride) floor covering
Domestic classification	EN ISO 10874	22 Domestic General Medium
Binder content	ISO 11638	Type I
Technical characteristics		
Total thickness	ISO 24346	2,6 mm
Wear layer thickness	ISO 24340	0,22 mm
Total weight	ISO 23997	1475 g/m ²
Roll Width		4 + 2 + 3 m
Roll Length	EN ISO 24341	30 m
Performance for CE Marking		
Declaration of Performance #	EN 14041	0132-0075-DOP-2020-01
Reaction to fire	EN 13501-1	Bfl-s1
Slip resistance	EN 13893 DIN 51130	$\mu \geq 0,30$ (DS) R 9 / R 10 * (depending on surface structure)
Electrostatical propensity	EN 1815	< 2 kV
Thermal resistance (in m ² •K/W)	ISO 10456 / EN 12524-1	0,04
Formaldehyde emission	EN 717-1	E1
Technical Performance		
Impact sound reduction - ΔL_w	EN ISO 717-2	16 dB
Residual indentation	ISO 24343-1	0.17 (best measured value)
Chemical resistance	ISO 26987	Not affected
Underfloor heating		Suitable (maximum 27°C)
Colour fastness to light	ISO 105-B02	≥ 6
Dimensional stability	ISO 23999	$\leq 0,20$ %
Sustainability, Environment & Indoor Air Quality		
Recyclable		Yes
French VOC rating		A+
Phthalate content		Phthalate-free
TVOC emissions after 28 days	EN 16516	Gold ($\leq 100 \mu\text{g} / \text{m}^3$)
Product ID		
Residential warranty (in years)		10
Surface treatment		Extreme Protection

The above information is subject to modification for the benefit of further improvement (2020-01).



Although the utmost care is taken, the data here given could be imprecise and liable to modifications of a technical nature. In its strive to improve its floor solutions, Tarkett reserves the right to modify their technical specifications, colours and materials at any moment and without prior notice.